

SERIE A DUE PISTONI PORTANTI TELESCOPICI TWO TELESCOPIC PISTONS RANGE

Tipo Type	Portata Capacity TON.	Portata sul 1° pistone Capacity on 1° piston TON.	A	B	C	D	E	Peso Weight KG.
DM 15	1,5	4	160	200	-	360	145X115	5
DM 15/P con piattello/with plate	1,5	4	190	200	-	390	145X115	5,5
DM 30	3	5	170	210	-	380	145X115	6
DM 30 B basso/low profile	3	5	140	145	-	285	145X115	5
DM 50	5	10	225	275	-	500	170X145	11
DM 100	10	20	230	310	-	540	195X170	14
DM 100/BUS	10	20	180	205	-	385	195X170	12
DM 150	15	25	230	310	-	540	200X170	18
DM 200	20	30	230	310	-	540	200X170	20
DM 250	25	40	240	310	-	550	235X210	22

Una gamma di sollevatori idraulici a bottiglia studiati e realizzati per ottenere un ingombro minimo, ed una maggiore corsa grazie ai pistoni telescopici. Struttura solida e compatta, e larga base di appoggio garantiscono estrema stabilità in tutte le posizioni di lavoro. Tutti i modelli vengono forniti con l'apposito manico di comando.

A range of hydraulic bottle jacks designed and manufactured for having a reduced minimum height, and a high lifting range thanks with their telescopic piston. Solid strong structure, and a wide support base, guarantee stability in all the correct operating position. All the models are supplied with an extension handle.

