


SOLLEVATORI OLEOPNEUMATICI A CARRELLO

PNEUMATIC TROLLEY JACK

Tipo Type	Portata Capacity TON.				Altezza minima Minim height mm.	A	B	C	D	E	F	G	H	I	L	M	N	Peso Weigth KG.
	P.1	P.2	P.3	P.4														
O.P. 203	60	30	20	-	180	250	315	400	-	110	155	800	1180	2210	340	1400	300	88
O.P. 114	60	30	20	11	180	250	315	400	477	110	155	800	1180	2210	340	1400	300	90
O.P. 154	75	40	30	15	146	205	253	290	355	110	155	800	1180	2230	340	1620	300	106



Studiati e realizzati per facilitare il sollevamento senza sforzo di grandi portate. Struttura solida e larga base di appoggio garantiscono estrema stabilità in tutte le posizioni di lavoro. Dotato di dispositivo di sicurezza per impedire la discesa del cilindro in caso di mancanza d'aria.

Valvola di sovraccarico e discesa pneumatica a depressione. Manico regolabile a tre posizioni.

Pressione d'esercizio bar 8-10. Attacco entrata aria 1/4" gas. Il modello O.P. 203 e O.P. 154 sono forniti completi di prolunghe standard.

Designed and developed to make easy lifting of great capacity. Strong body and large surface ensure the maximum stability in all working conditions. Provided with safety device to avoid the descent in case of air pressure lack. Supplied with automatic overload safety valve. Descent controlled by a pneumatic vacuum system.

Three position adjusting handle. Working pressure 8 - 10 bar. Air inlet 1/4" gas. The model O.P. 203 and O.P. 154 are supplied with two extension plates.

