

Su richiesta si producono brache su misura
e con portate superiori



CODICE	COLORE EN 1492-1 KG	β										
		0°-7°	7°-45°	45°-60°	UP TO 45	45°-60°	45°	45°	45°-60°	45°-60°	45°-60°	45°-60°
												
		1.0	0.8	2.0	1.4	1.0	0.7	0.5	1.4	1.12	1.0	0.8
BP	1000	1.0	0.8	2.0	1.4	1.0	0.7	0.5	1.4	1.12	1.0	0.8
BG	2000	2.0	1.6	4.0	2.8	2.0	1.4	1.0	2.8	2.24	2.0	1.6
BY	3000	3.0	2.4	6.0	4.2	3.0	2.1	1.5	4.2	3.36	3.0	2.4
BGY	4000	4.0	3.2	8.0	5.6	4.0	2.8	2.0	5.6	4.48	4.0	3.2
BR	5000	5.0	4.0	10.0	7.0	5.0	3.5	2.5	7.0	5.6	5.0	4.0
BB	6000	6.0	4.8	12.0	8.4	6.0	4.2	3.0	8.4	6.72	6.0	4.8
BBE	8000	8.0	6.4	16.0	11.2	8.0	5.8	4.0	11.2	8.96	8.0	6.4
BO	10000	10.0	8.0	20.0	14.0	10.0	7.0	5.0	14.0	11.2	10.0	8.0